

Green World Compounding  
 Parque Industrial de Alhama  
 C/ Alemania, s/n  
 30840 Alhama de Murcia  
 Murcia (España)  
 Tel: (+34) 968 63 22 21  
 Fax: (+34) 968 63 22 33  
 salvador.navarro@gwplastics-group.com  
 www.gwplastics-group.com

## Alfaten 130 Black

### Description

- Recycled medium-density polyethylene (MDPE) in pellet form
- Suitable for extrusion and injection process
- Source:
  - MDPE drip tape
- Applications:
  - Pipes & tubes, geomembrane liner, tarpaulin, injection moulding, construction & silage films, industrial additives,...

### Properties

	Method	Unit	Value Range
Density	UNE EN ISO 1183	g / cm <sup>3</sup>	0,93 – 0,95
MFI (190°C, 2'16kg)	UNE EN ISO 1133	g / 10min	0,3 – 0,5
Tensile Strain at Break	ISO 527-2	MPa	> 19
Elongation at break	ISO 527-2	%	> 600
Humidity	ISO 787/2	%	≤ 0,1
Ash content	ISO 3451-1, A	%	< 3
Color	Visual inspection	NA	Black

This information is offered in good faith and meant only as a guide. The transformer should take into account that it is a recycled material and subjected to some variations in their properties. Therefore, he is responsible for the processing conditions and the final use of the product.

Rev. Std  
 Date 18-08-2020  
 SNN

